



## Technische Daten

- Einfachwirkend
- Entlastet
- Drehrichtungsunabhängig
- Metallrollbalg
- nach EN 12756 (DIN24960)

## Einsatzgrenzen

d1 = 20 - 100 mm  
 p = 10 bar  
 t = -40 °C - 200 °C  
 vg = 20 m/s

## Werkstoffe

Gleitring: SIC (U32)  
 Elastomer: Viton (V)  
 Metallbalg: Edelstahl (E)  
 Andere Bauteile: Edelstahl (E)

d <sub>1</sub>	d <sub>3</sub>	l <sub>3</sub>
20	34,0	30,5
22	36,0	30,5
24	38,0	33,0
25	39,0	33,0
28	42,0	35,5
30	44,0	35,5
32	46,0	35,5
33	47,0	35,5
35	49,0	35,5
38	54,0	37,0
40	56,0	37,0
43	59,0	37,0
45	61,0	37,0
48	64,0	37,0
50	66,0	38,0
53	69,0	38,0
55	71,0	38,0
58	78,0	42,0
60	80,0	42,0
65	85,0	42,0
70	90,0	48,5
75	99,0	48,5
80	104,0	48,5
85	109,0	48,5
90	114,0	52,0
95	119,0	52,0
100	124,0	52,0

Änderungen jederzeit vorbehalten